DISPA®

100% Paper - 100% Recyclable - 100% Unique

THE UNIQUELY SUSTAINABLE, 100% PAPER DISPLAY BOARD

- DISPA® is the new paper board from 3A Composites, comprised of a uniquely laminated core of embossed/structured paper with flat, smooth facers ideal for printing
- The embossed structure that forms the central layer of DISPA gives it strength & rigidity, and prevents "read-through" or "fluting" that occurs when corrugate material is printed
- Excellent for digital and screen printing applications
- · Good for CNC cutting as well as die cutting
- Can be V-cut or creased and folded to create dimensional displays
- Extremely lightweight for easy handling & installation
- Good dimensional stability signs stay flat
- Fast, efficient, and easy processing even with hand tools
- Available in an interior and exterior grade product
- Made of 100% FSC® Certified paper (FSC® C169891)
- 100% Recyclable!

DISPA | A Uniquely Sustainable Solution

- Bright white, smooth paper surfaces provide excellent print results
- Ideal for pre-printed double-sided offset litho sheet lamination
- Excellent solution for short term, interior promotional campaigns

NEW! DISPA SIRIUS | Color Excellence in Digital Printing

- Premium paper facers with ColorPRO Technology optimized for digital printing
- Delivers sharp details, lines & text for clear, eye-catching graphics
- · Specialized paper designed for enhanced color saturation, rapid ink absorption, & fast dry time

NEW! DISPA OUTDOOR | For Short Term Exterior Applications

- Exterior grade paper suitable for short term, outdoor promotional signage & displays
- Smooth white paper facers provide high quality print results

APPLICATIONS

- POP / POS Displays
- Hanging Signage
- Window Displays
- Tradeshows & Exhibitions
- Promotional Campaigns
- Reprographics
- 3-Dimensional Displays
- Sophisticated Packaging
- Short term outdoor displays/signage (Exterior grade only)













DISPA



DISPASIRIUS



DISPA OUTDOOR







COMPOSITES

100% Paper - 100% Recyclable - 100% Unique

PRODUCT AVAILABILITY

	Gauges	Facers	Core	Sheet Sizes	
DISPA	3.8mm (0.15")	Bright White Coated Paper	White Embossed Paper	49.2" x 90" (1250mm x 2286mm)	
DISPA SIRIUS	3.3mm (0.13")	White Uncoated Paper with ColorPRO Technology	White Embossed Paper	B1 standard; (700mm x 1000mm / 27.6" x 39.4")	
DISPA OUTDOOR	2.2mm (0.09")	White Paper Facers	White Embossed Paper	49.2" x 90" (1250mm x 2286mm)	

TECHNICAL DATA	DISPA	DISPA SIRIUS	DISPA OUTDOOR		
Weight per Unit Area (approx.)	850 g/m ²	790 g/m²	760 g/m²		
Thickness	3.8 +/- 0.4mm	3.3mm +/- 0.4mm	2.2mm +/- 0.4mm		
Surface Smoothness	275 (ISO 5627)	11-12 (DIN 53107)	130 (ISO 5627)		
CIE L*a*b* (approx.) L* = brightness (0=black; 100=white) a* = red-green (-120=green; 120=red) b* = yellow-blue (-120=blue; 120=yellow)	L* = 94 a* = 0.4 b* = 1.5	L* = 94.3 a* = 1.1 b* = 1.9	L* = 92 a* = -0.1 b* = 2.0		
PH-value (Neutral = 7)	8.6 (DIN 53124)	8.6 (ISO 6588)	10 (ISO 6588)		
Bending (Flexural) Strength	3.5 N/mm² (DIN 53423)	3.0 N/mm² (EN 310)	8.0 N/mm² (EN 310)		
Width Tolerance	+/- 5mm				
Length Tolerance	+/- 5mm				

PROCESSING

- Printing: High quality results for UV-digital flatbed printing
- Cutting: Individual boards can be easily cut with a utility knife, or several can be cut with a guillotine or shear
- **CNC Processing**: For round shapes, an oscillating tool is recommended; for straight edges, drag tools are recommended; for V-groove cuts only new and sharp tools should be used.
- Laminating: Two-sided lamination is recommended; starch glue dries slower and the board retains its flatness better
- Gluing: Any kind of glue for paper can be used
- Hanging: Eyelets for banners are recommended



^{*}For additional processing guidelines, please refer to the complete Fabrication Guide on the website.